

Contact

LAN Systems (Nexans Cabling Solutions) Phone: +44 (0) 1256 486640 ncs.uk@nexans.com

Essential-6 Keystone Connector

Essential-6 Keystone Connector Screened Nexans ref.: N420.136

110Au110 10111 <u>14</u>

- · Complies with the latest Category 6 standards
- Easy termination without punchdown tool
- Keystone format
- Screened
- EMC rear cover for 360° shielding
- Also available without EMC rear cover
- Also available in unscreened version

Description

Application

The Nexans Essential-6 keystone connectors are manufactured and tested to the latest Category 6 specifications. They support Class E applications up to 250 MHz. When installed in conjunction with Nexans Category 6 cable, a 25 year Class E Link Certificate can be obtained from the Nexans web site.

Design

The Essential-6 screened keystone connectors are designed to match with Nexans Category 6 screened cable and patch cords and complement all Essential modular components, such as:

- keystone patch panels (black and white)
- · keystone outlet modules (UK, US and European formats)

Please follow the links on this page to view the related datasheets.

The modular jack is designed for keystone footprints of 14.78mm width, 20-20.78mm height and 1.5mm wall thickness and is compatible with a variety of keystone formatted structural hardware. (Please check compatibility with Nexans before using 3rd party hardware)

The Essential-6 connectors can be used with all types of Category 6 cable with solid wire from 24 to 22 AWG.

Performance

The Essential-6 keystone connectors are compliant with the specifications of ISO/ IEC 11801 and EN 50173.

Installation

The wire organiser guarantees fast and easy termination of the Essential-6 keystone connector without the need for a punchdown tool. An optional comfort tool (N420.567) can be used to increase the ease of installation.

This Essential-6 screened connector is supplied with a 360° EMC rear cover, which offers full protection against electromagnetic interference and at the same time allows easy termination of the cable drain wire.





Standards

International ISO/IEC 11801



Contact

LAN Systems (Nexans Cabling Solutions) Phone: +44 (0) 1256 486640 ncs.uk@nexans.com

Essential-6 Keystone Connector Essential-6 Keystone Connector Screened

- Fast and easy termination without punchdown tool
- Wiring according to colour code T568B or T568A
- Accepts 24, 23 and 22 AWG solid core cables
- Excellent EMC performance
- · Easy termination of drain wire
- Fits Nexans hardware designed for keystone format



Contact

LAN Systems (Nexans Cabling Solutions) Phone: +44 (0) 1256 486640 ncs.uk@nexans.com

Essential-6 Keystone Connector Essential-6 Keystone Connector Screened

Nexans ref.: N420.136

Characteristics

| Construction characteristics | |
|------------------------------|------------------------|
| Screen | Yes |
| Connector type | RJ45 and Tool-less IDC |
| Dimensional characteristics | |
| Width | 16.8 mm |
| Height | 24.2 mm |
| Depth | 36 mm |
| Usage characteristics | |
| Number of ports | 1 |
| Range | essential-6 |
| | |

Channel Performance

Values given for 2-connector channel, built with Essential-6 cable, outlet and patch panel.

| Frequency MHz | Insertion Loss dB/100m | NEXT PP dB | PS NEXT dB | ACR dB/100m | PS ACR dB/100m | ELFEXT dB/100m | PSELFEXT dB/100m | Return Loss dB |
|---------------|---------------------------|---------------|---------------|----------------|-------------------|-------------------|---------------------|-------------------|
| 1 | 4.0 | 65.0 | 62.0 | 65.0 | 62.0 | 63.3 | 60.3 | 19.0 |
| 4 | 4.2 | 63.0 | 60.5 | 58.9 | 56.4 | 51.2 | 48.2 | 19.0 |
| 10 | 6.6 | 56.6 | 54.0 | 50.0 | 47.4 | 43.3 | 40.3 | 19.0 |
| 16 | 8.3 | 53.2 | 50.6 | 44.9 | 42.3 | 39.2 | 36.2 | 18.0 |
| 20 | 9.3 | 51.6 | 49.0 | 42.3 | 39.7 | 37.2 | 34.2 | 17.5 |
| 31.25 | 11.7 | 48.4 | 45.7 | 36.7 | 34.0 | 33.4 | 30.4 | 16.5 |
| 62.5 | 16.9 | 43.4 | 40.6 | 26.5 | 23.7 | 27.3 | 24.3 | 14.0 |
| 100 | 21.7 | 39.9 | 37.1 | 18.2 | 15.4 | 23.3 | 20.3 | 12.0 |
| 155 | 27.6 | 36.7 | 33.8 | 9.1 | 6.2 | 19.5 | 16.5 | 10.1 |
| 200 | 31.7 | 34.8 | 31.9 | 3.1 | 0.1 | 17.2 | 14.2 | 9.0 |
| 250 | 35.9 | 33.1 | 30.2 | -2.8 | -5.8 | 15.3 | 12.3 | 8.0 |

All values are specified at 20°C.