



KFT08T5

8w CFL EXUN T5, 288mm, 20000hrs, 4000k



Product Overview

A comprehensive range of compact fluorescent T5 (High Efficiency) tubes with premium specifications. Designed for use in a wide variety of commercial and industrial applications such as offices, warehouses and supermarkets, these tubes deliver a high lumen to watt ratio and are extremely robust and durable.

Features

High luminous efficacy of up to 94lm/W.

High efficiency tri-phosphor coating with excellent colour rendering.

Robust and with a long service life.

Long life of 20,000hrs.

Free of liquid mercury, minimising environmental impact by employing amalgam.

Unit D2 Kennetside, Bone Lane
Newbury, Berkshire

T: 01635 523 713 E: sales@kosnic.com W: <http://www.kosnic.com>

Specifications

KFT08T5/840	
Fitting	G5
Shape / Type	T5 (High Efficiency)
Colour Finish	White
Optics Type	Tri-phosphor Coating
Wattage (w)	8
Total Lumens (lm)	450
Input Voltage	230V
CCT Temperature (k)	4000
CCT Name	Cool White
Rated Life (hrs)	20000
CRI	82
Dimmable	No
Length (mm)	16
Width (mm)	288
Depth (mm)	16
Ambient Temperature (°C)	-20 to 40
Barcode	5060063422060

Energy Label

KFT08T5/840	
Energy Class	A
Energy Consumption (kWh/1000h)	9

Packaging

KFT08T5/840	
Outer Box Length (mm)	330
Outer Box Width (mm)	200
Outer Box Height (mm)	205
Volume	0.01353
Box Quantity	100
Outer Box Weight (kg)	4.5

Datasheet generated from <http://www.electrika.com> last updated Tuesday, May 15, 2018 11:28:40 AM